

# IEC 309 PIN & SLEEVE DEVICES • LIGHT & STAGE DEVICES



## Well hidden from View!

It is necessary that electrical installations on stages function without interruption and not be a distraction to the viewers.

## The Walther Electric Solution:

Black devices which prevent bothersome light reflections and thus make the electrical installation on stages almost "invisible"!

Standard Style













New Light & Stage Style



Now You See It

Now You Don't

## Male Plugs IP 44 for Light & Stage Applications IEC/EN 60 309

		   2 P + E   3 P + E   3 P + N + E			Amperage	Poles	<b>110 V</b> 50 a. 60 Hz <small>3pole 4pole 5pole</small> <small>4h 4h 4h</small>	<b>230 V</b> 50 a. 60 Hz <small>3pole 4pole 5pole</small> <small>6h 9h 9h</small>	<b>400 V</b> 50 a. 60 Hz <small>3pole 4pole 5pole</small> <small>9h 6h 6h</small>	<b>500 V</b> 50 a. 60 Hz <small>3pole 4pole 5pole</small> <small>7h 7h 7h</small>		
Part numbers												
	16	3					<b>211 306 SW</b>				10	112
	16	4						<b>211 406 SW</b>			10	154
	16	5						<b>211 SW</b>			10	170
	32	3					<b>231 306 SW</b>				10	211
	32	4						<b>231 406 SW</b>			10	217
	32	5						<b>231 SW</b>			10	240
	63	3					<b>261 306 SW</b>				5	475
	63	4						<b>261 406 SW</b>			5	566
	63	5						<b>261 SW</b>			5	613
	125	3					<b>279 306 SW<sup>1)</sup></b>				2	1185
125	4							<b>279 406 SW<sup>1)</sup></b>		2	1329	
125	5							<b>279 SW<sup>1)</sup></b>		2	1473	
231SW	<b>Plugs with gland entry, in 16 - 63 A = IP 44 , in 125 A = IP 67  1)</b>											
	16	3	215 304 SW				<b>215 306 SW</b>				10	101
	215306SW	<b>Plugs IP 44  with inverted cable entry</b>										
	16	5						<b>210 SW</b>			10/60	176
	32	5						<b>230 SW</b>			10/60	250
230SW	<b>Plugs IP 44 , with cable gland</b>											

Consult customer service for other amperage and voltage ratings and configurations.



## Female Connectors & Socket-Outlets IP 44 for Light & Stage Applications IEC/EN 60 309

  		Amperage	Poles	110 V	230 V	400 V	500 V	 	
2 P+E	3 P+E			3 P+N+E	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz		50 a. 60 Hz
				3pole 4h   4pole 4h   5pole 4h	3pole 6h   4pole 9h   5pole 9h	3pole 9h   4pole 6h   5pole 6h	3pole 7h   4pole 7h   5pole 7h		
Part numbers									
	16	3			311 306 SW			10	147
	16	4				311 406 SW		10	197
	16	5				311 SW		10	214
	32	3			331 306 SW			10	265
	32	4				331 406 SW		10	278
	32	5				331 SW		10	300
	63	3			361 306 SW			5	656
	63	4				361 406 SW		5	771
	63	5				361 SW		5	787
	125	3			379 306 SW <sup>2)</sup>			2	1362
	125	4				379 406 SW <sup>2)</sup>		2	1536
	125	5				379 SW <sup>2)</sup>		2	1710
331306SW	Couplers with gland entry, 16 - 63 A = IP 44  , 125 A = IP 67  <sup>2)</sup>								
	16	3	315 304 SW		315 306 SW			10	140
	315306SW	Couplers IP 44  , with inverted cable entry							
	16	5				310 SW		10/60	219
	32	5				330 SW		10/60	311
310SW	Couplers IP 44  , with cable gland								
	16	3	410 304 SW		410 306 SW			10	128
	16	4				410 406 SW		10	106
	16	5				410 SW		10	165
	32	3			430 306 SW			10	208
	32	4				430 406 SW		10	215
	32	5				430 SW		10	226
	63	3			460 306 SW			5	586
	63	4				460 406 SW		5	645
	63	5				460 SW		5	776
	125	3			479 306 SW <sup>3)</sup>			2	990
	125	4				479 406 SW <sup>3)</sup>		2	1155
	125	5				479 SW <sup>3)</sup>		2	1319
430SW	Panel sockets, straight, 16 - 63 A = IP 44  , 125 A = IP 67  <sup>3)</sup> , fingerproof acc. to BGV A2								

Consult customer service for other amperage and voltage ratings and configurations.