

NEW PRODUCT - NEW CEE_{typ} GENERATION



Standard screw-terminal version: faster and safer



Cable gland: Automatic strain relief plus sealing all in one go



Double safety: two contact screws for vibration-proof wiring



Color coding: safe identification of conductors



The standard version: with screw terminals

Doubly safe: with 2 connection screws per terminal

Automatic cable gland: the absolutely safe solution

Example for 6 h types

Former part nos.: Today's part no.:

| | | |
|-----|---|-----|
| 210 | ▶ | 210 |
| 211 | | 210 |
| 212 | | 210 |
| 310 | ▶ | 310 |
| 311 | | 310 |
| 312 | | 310 |
| 230 | ▶ | 230 |
| 231 | | 230 |
| 232 | | 230 |
| 330 | ▶ | 330 |
| 331 | | 330 |
| 332 | | 330 |








High technology moulding, a patented WALTHER system for perfect sealing

For expert safety: totally splashproof, including strain relief

Durable locking: Fasten front and back part until audible snap

ORDERING INFORMATION

|  3 P + N + E | Ampère | Poles | 110 V | 230 V | 400 V | Conductor cross section | Cable diameter |  |  | |
|--|--------|-------|----------------------------|----------------------------|----------------------------|-------------------------|----------------|---|---|--|
| | | | 50 a. 60 Hz 5pole 4h | 50 a. 60 Hz 5pole 9h | 50 a. 60 Hz 5pole 6h | | | | | |
| Part numbers | | | | | | | | | | |
|  pic. 210 | 16 | 5 | 210 504 | 210 509 | 210 | 1 - 4 mm ² | 7,5 - 19,5 mm | 10/60 | 176 | |
| | 32 | 5 | 230 504 | 230 509 | 230 | 2,5 - 6 mm ² | 10 - 24,5 mm | 10/60 | 250 | |
| CEE Male Plug Δ IP 44, with screw terminals | | | | | | | | | | |
|  pic. 310 | 16 | 5 | 310 504 | 310 509 | 310 | 1 - 4 mm ² | 7,5 - 19,5 mm | 10/60 | 219 | |
| | 32 | 5 | 330 504 | 330 509 | 330 | 2,5 - 6 mm ² | 10 - 24,5 mm | 10/60 | 311 | |
| CEE Female Connector (coupler) Δ IP 44, with screw terminals | | | | | | | | | | |

Consult customer service for other amperage and voltage ratings and configurations.

WATERTIGHT PLUGS AND CONNECTORS IP67



The New Walther Watertight Solution!

The new style Walther IP67 plugs and connectors have improved sealing, fast, safe and tight cable gland. The new Walther IP67 plugs and connectors also offer a provision for a padlock to comply with OSHA Lockout/Tagout requirements.



Double sealing groove:
For a larger sealing surface and thus higher tightness.



Protecting cap:
The cap is always at hand since it is undetachably fixed on the bayonet ring

Padlockable:
Protection against unauthorized disconnection from the electric circuit. Stay OSHA Compliant!


Modes of Connection

You can choose between:

■ **screw terminals:**
2 connection screws per contact, already with 16 A - for double safety



■ **screwless version:**
Centrepiece is the distributor ring. When inserting the wires into the slots they are bent by 180°. This serves as anchor. By inserting the distributor ring into the front part and screwing down the back part all wires are contacted in one go.



New Product Features

- Pleasing product design
- Cable gland for better strain relief and tightness.
- Opened hinged lid snaps automatically into closed position when let loose. Thereby increased contact protection even when lid is not yet screwed down.
- Unlimited strain relief with the screwless version - nobody will be able to pull this cable out anymore.
- Padlockable - as protection against unauthorized disconnection from the circuit
- Double sealing groove for more tightness
- Captive protecting cap

Assembly








- Just screw front and back part together - ready.
- Only screw down cable gland - quick and easy.
- To attach the padlock simply insert its shackle into the hole on the bayonet ring
- Plug and socket, 16 A and 32 A
- Protecting cap (accessory)
- padlock (accessory)

WATERTIGHT PLUGS AND CONNECTORS IP67



CEEtyp Plugs and Sockets

Range of products

|    2P+E 3P+E 3P+N+E | | Ampère | Poles | 110 V 50 a. 60 Hz <small>3pole 4pole 5pole 4h 4h 4h</small> | 230 V 50 a. 60 Hz <small>3pole 4pole 5pole 6h 9h 9h</small> | 400 V 50 a. 60 Hz <small>3pole 4pole 5pole 9h 6h 6h</small> | Conductor cross section | Cable diameter |   |
|---|----|--------|------------|--|--|--|-------------------------|----------------|---|
| Part Numbers | | | | | | | | | |
|  | 16 | 4 | 219 404 | 219 409 | 219 406 | 1 - 2,5 mm ² | 7,5 - 18,5 mm | 10 | 212 |
| | 16 | 5 | 219 504 | 219 509 | 219 | | | 10 | 236 |
| | 32 | 3 | 239 304 | 239 306 | 239 309 | 2,5 - 6 mm ² | 10 - 22,5 mm | 10 | 290 |
| | 32 | 4 | 239 404 | 239 409 | 239 406 | | | 10 | 300 |
| | 32 | 5 | 239 504 | 239 509 | 239 | | | 10 | 340 |
| | 16 | 4 | 219 404 SL | 219 409 SL | 219 406 SL | 1 - 2,5 mm ² | 7,5 - 18,5 mm | 10 | 212 |
| | 16 | 5 | 219 504 SL | 219 509 SL | 219 SL | | | 10 | 236 |
| | 32 | 3 | 239 304 SL | 239 306 SL | 239 309 SL | 2,5 - 6 mm ² | 10 - 22,5 mm | 10 | 290 |
| | 32 | 4 | 239 404 SL | 239 409 SL | 239 406 SL | | | 10 | 300 |
| | 32 | 5 | 239 504 SL | 239 509 SL | 239 SL | | | 10 | 340 |
| Fig. 219 CEE Plug IP 67, with screw terminals | | | | | | | | | |
|  | 16 | 4 | 319 404 | 319 409 | 319 406 | 1 - 2,5 mm ² | 7,5 - 18,5 mm | 10 | 268 |
| | 16 | 5 | 319 504 | 319 509 | 319 | | | 10 | 298 |
| | 32 | 3 | 339 304 | 339 306 | 339 309 | 2,5 - 6 mm ² | 10 - 22,5 mm | 10 | 351 |
| | 32 | 4 | 339 404 | 339 409 | 339 406 | | | 10 | 369 |
| | 32 | 5 | 339 504 | 339 509 | 339 | | | 10 | 415 |
| | 16 | 4 | 319 404 SL | 319 409 SL | 319 406 SL | 1 - 2,5 mm ² | 7,5 - 18,5 mm | 10 | 268 |
| | 16 | 5 | 319 504 SL | 319 509 SL | 319 SL | | | 10 | 298 |
| | 32 | 3 | 339 304 SL | 339 306 SL | 339 309 SL | 2,5 - 6 mm ² | 10 - 22,5 mm | 10 | 351 |
| | 32 | 4 | 339 404 SL | 339 409 SL | 339 406 SL | | | 10 | 369 |
| | 32 | 5 | 339 504 SL | 339 509 SL | 339 SL | | | 10 | 415 |
| Fig. 319 CEE Couplers IP 67, with screw terminals | | | | | | | | | |

Consult customer service for other amperage and voltage ratings and configurations.

* "SL" UL Listing Pending