



Ampère	Poles	110 V 50 a. 60 Hz			230 V 50 a. 60 Hz			400 V 50 a. 60 Hz			500 V 50 a. 60 Hz			> 50 - 500 V 100 - 300 Hz			> 50 - 500 V over 300 - 500 Hz				
		3pole 4h	4pole 4h	5pole 4h	3pole 6h	4pole 9h	5pole 9h	3pole 9h	4pole 6h	5pole 6h	3pole 7h	4pole 7h	5pole 7h	3pole 10h	4pole 10h	5pole 10h	3pole 2h	4pole 2h	5pole 2h		

Part numbers

	16	4	210 404 SL	210 409 SL	210 406 SL	210 407 SL	210 410 SL	210 402 SL	10/60	200
	16	5	210 504 SL	210 509 SL	210 SL				10/60	220
	32	3	230 304 SL	230 306 SL	230 309 SL				10/60	260
	32	4	230 404 SL	230 409 SL	230 406 SL	230 407 SL	230 410 SL	230 402 SL	10/60	282
	32	5	230 504 SL	230 509 SL	230 SL				10/60	304
	Screwless plugs with IDC (insulation displacement connection), ⚠ IP 44, with cable gland									

	16	3	210 304 CK	210 306 CK	▶ CK = plugs with crimp contacts, screwless, click-together assembly, nonrewireable, tamper proof, maintenance-free					10/10	113
	16	3	210 304 SK	210 306 SK	▶ SK = plugs with screw terminals, rewireable					10/10	124

Plugs ⚠ IP 44 either with crimp contacts (CK) or with screw terminals (SK)

	16	4	210 404	210 409	210 406	210 407	210 410	210 402	10	196
	16	5	210 504	210 509	210				10/60	212
	32	3	230 304	230 306	230 309				10	253
	32	4	230 404	230 409	230 406	230 407	230 410	230 402	10	274
	32	5	230 504	230 509	230				10/60	303
	Plugs ⚠ IP 44, with screw terminals, with cable gland									

	16	3	212 304	212 306	212 309	<i>(flexible cable gland, eye hook for padlock)</i>			10	113
	16	3	215 304	215 306	215 309	<i>(with inverted cable entry)</i>			10	101

Plugs ⚠ IP 44

	16	3	211 304	211 306	211 309				10	112	
	16	4	211 404	211 409	211 406	211 407	211 410	211 402	10	154	
	16	5	211 504	211 509	211				10	170	
	16	5	211 NI <i>(with nickel plated contacts + glass-fibre reinforced enclosure)</i>							10	199
	32	3	231 304	231 306	231 309				10	211	
	32	4	231 404	231 409	231 406	231 407	231 410	231 402	10	217	
	32	5	231 504	231 509	231				10	240	
	32	5	231 NI <i>(with nickel plated contacts + glass-fibre reinforced enclosure)</i>							10	286
	63	3	261 304	261 306	261 309				5	475	
	63	4	261 404	261 409	261 406	261 407	261 410	261 402	5	566	
63	5	261 504	261 509	261				5	613		
63	5	261 NI <i>(with nickel plated contacts + glass-fibre reinforced enclosure)</i>							5	613	

Plugs ⚠ IP 44, with gland entry

	16	3	210 304	210 306	210 309				10	111	
	16	5	210 NI <i>(with nickel plated contacts + glass-fibre reinforced enclosure)</i>							10	177
	32	5	230 NI <i>(with nickel plated contacts + glass-fibre reinforced enclosure)</i>							10	253
	63	3	260 304	260 306	260 309				5	475	
	63	4	260 404	260 409	260 406	260 407	260 410	260 402	5	527	
	63	5	260 504	260 509	260				5	575	
	63	5	260 NI <i>(with nickel plated contacts + glass-fibre reinforced enclosure)</i>							5	579
	Plugs ⚠ IP 44, with screw terminals, with flexible cable entry										



Ampère	Poles	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	> 50 - 500 V 100 - 300 Hz	> 50 - 500 V over 300 - 500 Hz		
		3pole 4h 4pole 4h pole 4h	3pole 6h 4pole 9h 5pole 9h	3pole 9h 4pole 6h 5pole 6h	3pole 7h 4pole 7h 5pole 7h	3pole 10h 4pole 10h 5pole 10h	3pole 2h 4pole 2h 5pole 2h		

Part numbers



16	3	216 304	216 306	216 309				10	106
16	4	216 404	216 409	216 406	216 407	216 410	216 402	10	150
16	5	216 504	216 509	216				10/60	163
32	3	236 304	236 306	236 309				10	214
32	4	236 404	236 409	236 406	236 407	236 410	236 402	10	230
32	5	236 504	236 509	236				10	251

236 mondo plugs ⚠ IP 44, angled, back part RAL 7035 light grey



16	5			210 PH				10	180
16	5			210 PHNI	(with nickel plated contacts + glass-fibre reinforced enclosure)			10	183
32	5			230 PH				10	257
32	5			230 PHNI	(with nickel plated contacts + glass-fibre reinforced enclosure)			10	264

230 PH Phase inverters ⚠ IP 44, with flexible cable entry



16	5			211 PH				10	174
16	5			211 PHNI	(with nickel plated contacts + glass-fibre reinforced enclosure)			10	180
32	5			231 PH				10	245
32	5			231 PHNI	(with nickel plated contacts + glass-fibre reinforced enclosure)			10	257

231 PH Phase inverters ⚠ IP 44, with gland entry



16	4			210 406 DF	for voltage ranges of 110 V - 690 V			10	144
16	5			210 DF				10	173
32	4			230 406 DF				10	198
32	5			230 DF				10	241
63	4			260 406 DF				10	603
63	5			260 DF				5	685

230DF Phase sequence control plugs ⚠ IP 44



16	3	219 304	219 306	219 309	(with gland entry and screw terminals)			10	133
----	---	---------	----------------	---------	--	--	--	----	-----

All red marked plugs come with new design and cable gland. Additionally these are also available as screwless version with IDC insulation displacement connection. To order a plug as screwless version, just add „SL“ to the part number, e.g. 219SL.

16	4	219 404	219 409	219 406	219 407	219 410	219 402	10	212
16	5	219 504	219 509	219				10	236
32	3	239 304	239 306	239 309				10	290
32	4	239 404	239 409	239 406	239 407	239 410	239 402	10	300
32	5	239 504	239 509	239				10	340

Plugs 💧 IP 67, with screw terminals or as screwless SL version with insulation displacement technique



16	5			219 NI				10	199
32	5			239 NI	(with nickel plated contacts and glass-fibre reinforced enclosure)			10	286
63	5			269 NI				5	771
125	5			279 NI				2	1473
63	3	269 304	269 306	269 309				5	501
63	4	269 404	269 409	269 406	269 407	269 410	269 402	5	623
63	5	269 504	269 509	269				5	668
125	3	279 304	279 306	279 309				2	1185
125	4	279 404	279 409	279 406	279 407	279 410	279 402	2	1329
125	5	279 504	279 509	279				2	1473

269 Plugs 💧 IP 67, with gland entry


Availability of blue printed (or not listed) frequencies and voltages up to 690 V on request!

Other voltages and frequencies on request. Part numbers in bold letters are standard versions.




Ampère	Poles	110 V 50 a. 60 Hz			230 V 50 a. 60 Hz			400 V 50 a. 60 Hz			500 V 50 a. 60 Hz			> 50 - 500 V 100 - 300 Hz			> 50 - 500 V over 300 - 500 Hz		
		3pole 4h	4pole 4h	5pole 4h	3pole 6h	4pole 9h	5pole 9h	3pole 9h	4pole 6h	5pole 6h	3pole 7h	4pole 7h	5pole 7h	3pole 10h	4pole 10h	5pole 10h	3pole 2h	4pole 2h	5pole 2h




Part numbers												
	16	3	610 304	610 306	610 309					10	126	
	16	4	610 404	610 409	610 406	610 407	610 410	610 402		10	164	
	16	5	610 504	610 509	610					10/60	177	
	16	5	610 NI (with nickel plated contacts + glass-fibre reinforced enclosure)								10	180
	16	5	610 PH (with phase inverter)								10	184
	16	5	610 PHNI (with phase inverter, nickel plated contacts and glass-fibre reinforced enclosure)								10	180
	32	3	630 304	630 306	630 309					10	219	
	32	4	630 404	630 409	630 406	630 407	630 410	630 402		10	237	
	32	5	630 504	630 509	630					10	256	
	32	5	630 NI (with nickel plated contacts + glass-fibre reinforced enclosure)								10	261
32	5	630 PH (with phase inverter)								10	264	
32	5	630 PHNI (with phase inverter, nickel plated contacts and glass-fibre reinforced enclosure)								10	261	


630 Wall mount appliance inlets  IP 44, external fixing means, 1 top cable entry

	16	4	616 404	616 409	616 406	616 407	616 410	616 402	5	323
	16	5	616 504	616 509	616				5	352
	32	3	636 304	636 306	636 309				5	349
	32	4	636 404	636 409	636 406	636 407	636 410	636 402	5	372
	32	5	636 504	636 509	636				5	399


636 Wall mount appliance inlets  IP 44, internal fixing means, 2 cable entries top & bottom

	16	3	611 304	611 306	611 309				10	122	
	16	4	611 404	611 409	611 406	611 407	611 410	611 402	10	176	
	16	5	611 504	611 509	611				10	207	
	16	5	611 PH (with phase inverter)							10	205
	16	5	611 PHNI (with phase inverter, nickel plated contacts and glass-fibre reinforced enclosure)							10	180
	32	3	631 304	631 306	631 309				10	230	
	32	4	631 404	631 409	631 406	631 407	631 410	631 402	10	293	
	32	5	631 504	631 509	631				10	276	
	32	5	631 PH (with phase inverter)							10	283
	32	5	631 PHNI (with phase inverter, nickel plated contacts and glass-fibre reinforced enclosure)							10	261
63	3	661 304	661 306	661 309					5	456	
63	4	661 404	661 409	661 406	661 407	661 410	661 402		5	513	
63	5	661 504	661 509	661					5	553	

631 Panel mount appliance inlets IP 44  , right-angled, flange screwed on

	16	3	615 304	615 306	615 309				10	94	
	16	4	615 404	615 409	615 406	615 407	615 410	615 402	10	131	
	16	5	615 504	615 509	615				10	145	
	16	5	615 PH (with phase inverter)							10	145
	32	3	635 304	635 306	635 309				10	150	
	32	4	635 404	635 409	635 406	635 407	635 410	635 402	10	166	
32	5	635 504	635 509	635				10	191		
32	5	635 PH (with phase inverter)							10	191	

635 Panel mount appliance inlets IP 44  , straight, flange screwed on

	16	3	612 306 (white)						1	242
	16	3	613 306 (brown)	(fastening frame also serving as template for drilling holes)					1	242
	16	3	614 306 (black)						1	242

612306 Caravan built-in appliance inlets, IP 44 



Ampère	Poles	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	> 50 - 500 V 100 - 300 Hz	> 50 - 500 V over 300 - 500 Hz		
		3pole 4h 4pole 4h 5pole 4h	3pole 6h 4pole 9h 5pole 9h	3pole 9h 4pole 6h 5pole 6h	3pole 7h 4pole 7h 5pole 7h	3pole 10h 4pole 10h 5pole 10h	3pole 2h 4pole 2h 5pole 2h		

Part numbers



638	16	3	618 304	618 306	618 309				5	357
		4	618 404	618 409	618 406	618 407	618 410	618 402	5	328
		5	618 504	618 509	618				5	357
	32	3	638 304	638 306	638 309				5	421
		4	638 404	638 409	638 406	638 407	638 410	638 402	5	427
		5	638 504	638 509	638				5	463

Wall mount appliance inlets IP 67, internal fixing



639	16	3	619 304	619 306	619 309				10	195
		4	619 404	619 409	619 406	619 407	619 410	619 402	10	206
		5	619 504	619 509	619				10	217
	16	5				619 NI (with nickel plated contacts + glass-fibre reinforced enclosure)			10	205
	32	3	639 304	639 306	639 309				5	223
		4	639 404	639 409	639 406	639 407	639 410	639 402	5	259
		5	639 504	639 509	639				5	295
	32	5				639 NI (with nickel plated contacts + glass-fibre reinforced enclosure)			10	295
	63	3	669 304	669 306	669 309				5	525
		4	669 404	669 409	669 406	669 407	669 410	669 402	5	569
		5	669 504	669 509	669				5	613
		5				669 NI (with nickel plated contacts + glass-fibre reinforced enclosure)			5	613

Panel mount appliance inlets IP 67, right-angled, flange screwed on



668	63	3	668 304	668 306	668 309				2	825
		4	668 404	668 409	668 406	668 407	668 410	668 402	2	827
		5	668 504	668 509	668				2	891

Wall mount appliance inlets IP 67, external fixing, 1 top cable entry



678	125	3	678 304	678 306	678 309				1	2700
		4	678 404	678 409	678 406	678 407	678 410	678 402	1	3005
		5	678 504	678 509	678				1	3800
	125	3	678 304 OK	678 306 OK	678 309 OK				1	860
		4	678 404 OK	678 409 OK	678 406 OK	678 407 OK	678 410 OK	678 402 OK	1	1455
		5	678 504 OK	678 509 OK	678 OK	OK = without terminal block set			1	2250

Wall mount appliance inlets IP 67, internal fixing, with terminal block set (OK version without terminal block set)



679	125	3	679 304	679 306	679 309				2	673
		4	679 404	679 409	679 406	679 407	679 410	679 402	2	910
		5	679 504	679 509	679				2	1147

Panel mount appliance inlets IP 67, straight, flange screwed on