



Well hidden from View!

It is necessary that electrical installations on stages function without interruption and not be a distraction to the viewers.

The Walther Electric Solution:

Black devices which prevent bothersome light reflections and thus make the electrical installation on stages almost "invisible"!

Standard Style

New Light & Stage Style



Now You See It

Now You Don't

Male Plugs IP 44 for Light & Stage Applications

IEC/EN 60 309



2 P+E

3 P+E

3 P+N+E

Amperage

Poles

110 V

50 a. 60 Hz

3pole 4pole 5pole
4h 4h 4h

230 V

50 a. 60 Hz

3pole 4pole 5pole
6h 9h 9h

400 V

50 a. 60 Hz

3pole 4pole 5pole
9h 6h 6h








500 V

50 a. 60 Hz

3pole 4pole 5pole
7h 7h 7h



Part numbers

 <p>231SW</p>	16	3		211 306 SW		10	112
	16	4			211 406 SW	10	154
	16	5			211 SW	10	170
	32	3		231 306 SW		10	211
	32	4			231 406 SW	10	217
	32	5			231 SW	10	240
	63	3		261 306 SW		5	475
	63	4			261 406 SW	5	566
	63	5			261 SW	5	613
	125	3		279 306 SW¹⁾		2	1185
125	4			279 406 SW¹⁾	2	1329	
125	5			279 SW¹⁾	2	1473	
Plugs with gland entry, in 16 - 63 A = IP 44 , in 125 A = IP 67  ¹⁾							
 <p>215306SW</p>	16	3	215 304 SW	215 306 SW		10	101
	Plugs IP 44  with inverted cable entry						
 <p>230SW</p>	16	5			210 SW	10/60	176
	32	5			230 SW	10/60	250
Plugs IP 44 , with cable gland							

Consult customer service for other amperage and voltage ratings and configurations.



Female Connectors & Socket-Outlets IP 44 for Light & Stage Applications IEC/EN 60 309

 2 P+E  3 P+E  3 P+N+E			Amperage	Poles	110 V 50 a. 60 Hz <small>3pole 4pole 5pole</small> <small>4h 4h 4h</small>	230 V 50 a. 60 Hz <small>3pole 4pole 5pole</small> <small>6h 9h 9h</small>	400 V 50 a. 60 Hz <small>3pole 4pole 5pole</small> <small>9h 6h 6h</small>	500 V 50 a. 60 Hz <small>3pole 4pole 5pole</small> <small>7h 7h 7h</small>		
Part numbers										
	16	3				311 306 SW			10	147
	16	4					311 406 SW		10	197
	16	5					311 SW		10	214
	32	3				331 306 SW			10	265
	32	4					331 406 SW		10	278
	32	5					331 SW		10	300
	63	3				361 306 SW			5	656
	63	4					361 406 SW		5	771
	63	5					361 SW		5	787
	125	3				379 306 SW²⁾			2	1362
	125	4					379 406 SW²⁾		2	1536
	125	5					379 SW²⁾		2	1710
331306SW	Couplers with gland entry, 16 - 63 A = IP 44 , 125 A = IP 67  ²⁾									
	16	3	315 304 SW			315 306 SW			10	140
	315306SW	Couplers IP 44 , with inverted cable entry								
	16	5					310 SW		10/60	219
	32	5					330 SW		10/60	311
310SW	Couplers IP 44 , with cable gland									
	16	3	410 304 SW			410 306 SW			10	128
	16	4					410 406 SW		10	106
	16	5					410 SW		10	165
	32	3				430 306 SW			10	208
	32	4					430 406 SW		10	215
	32	5					430 SW		10	226
	63	3				460 306 SW			5	586
	63	4					460 406 SW		5	645
	63	5					460 SW		5	776
	125	3				479 306 SW³⁾			2	990
	125	4					479 406 SW³⁾		2	1155
	125	5					479 SW³⁾		2	1319
430SW	Panel sockets, straight, 16 - 63 A = IP 44 , 125 A = IP 67  ³⁾, fingerproof acc. to BGV A2									

Consult customer service for other amperage and voltage ratings and configurations.