

## **Dual Utility Pedestal**





Dual utility receptacles mounted on a stainless steel pedestal are perfect for refrigeration areas, processing areas, wash-down areas and more. Receptacles can withstand varying temperatures and be custom designed for different IP ratings depending on the application

- Rugged, weather resistant plastic enclosure for Indoor/Outdoor use (NEMA 3R)
- All output connectors are circuit breaker protected for added safety
- Stainless steel pedestal to protect mechanical interlock and GFCI duplex

## **SPECIFICATIONS**

SPECIFICATIONS	30A/480V ~ 3 Phase
RATING	20A/120V ~ 1 Phase
ENVIRONMENTAL RATING	NEMA 3R
INPUT 1	20A/120V, 1P+N+G (Hard wire)
INPUT 2	30A/480V, 3P+G (Hard wire)
OUTPUT 1	(1) 20A/120V GFCI Duplex
OUTPUT 2	(1) 30A/480V IEC 60309 IP67, 3P+G
CIRCUIT 2 Protection	32A, 3 Pole, IP67
	Mechanical Interlock Switch
SWITCH	32A/480V, 3 Pole, IP67
DIMENSIONS	L 8" W 9" H 58"
WFIGHT	29 lbs.

## **ACCESSORIES**

Ask about matching cable assemblies or custom configurations





Note: All Specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437 rev 220112

