

PRODUCT DATA SHEET

| | |
|--------------|-------------------|
| Part Numbers | 239409 & AT139409 |
|--------------|-------------------|

| | | |
|--------------|--------|---------------|
| EAN | 239409 | 4015609014378 |
| Manufacturer | 239409 | Walther-Werke |
| WEEE-Reg-Nr | 239409 | DE 22131895 |

Walther Electric 239409 Male Plug 30A 4P 9H with External Cable Gland & AT139409 Wall Socket with 3-Pole Switch and Interlocking

The **AT139409** non-metallic enclosure combines a wall mounted electrical socket with a switched safety device to ensure that the electrical circuit is de-energized for service or maintenance. The switch is Lockout/Tagout compliant with OSHA regulations providing a degree of protection to personnel against accidental contact with live electrical equipment.

- **Rated IP67 Dust-Tight & Watertight for demanding environments**
- **NEMA 4X Watertight (for IP67 Interlocks)**
- **OSHA Lockout/Tagout Compliant**
- **Twist Locking Ring with Gasket**
- **Color-Coded for added safety**

Perfect for motor line-of-sight installations in handling & sorting areas, storage & shipping, processing lines, packaging, or anywhere you need large and permanently wired equipment.

Ordering/Logistics Information

| | AT139409 | 239409 |
|------------------------|---------------------|---------------------|
| Order Unit | Piece | Piece |
| Customs Number | 85366990 | 85366990 |
| Net Weight | 2.30 lbs or 1.04 kg | 0.66 lbs or 0.3 kg |
| Packing Quantity (VPE) | 1 | 10 |
| Packaging Length | 9.125 in or 0.23 m | 12.10 in or 0.31 m |
| Packaging Width | 6.125 in or 0.16 m | 10.04 in or 0.255 m |
| Packaging Depth | 4.5 in or 0.11 m | 5.91 in or 0.15 m |
| Gross Weight (VPE) | 2.5 lbs or 1.13 kg | 7.05 lbs or 3.20 kg |



Certification

| | AT139409 | 239409 |
|------------------------|-----------------|-----------------------|
| VDE/ENEC Certification | 40000374 | 40021520 |
| UL Certification | E188992/E196679 | E329476 |
| EAC Certification | n/a | BY112.02.01.020.06090 |

Classification System

| | | |
|-----------------------|-----|----------|
| Classification System | n/a | ETIM_7.0 |
| ETIM Class | n/a | EC000140 |

Technical Product Data

| | | |
|---------------------------------|----------------------|----------------------|
| Width | 6.06 in or 154 mm | 3.625 in or 0.09 m |
| Height | 4.45 in or 113 mm | 3.625 in or 0.09 m |
| Length | 8.46 in or 215 mm | 7.125 in or 0.18 m |
| IEC-Amperage | 32 A | 32 A |
| Amperage according to UL/CSA | 30 A | 30 A |
| Number of Poles | 4 | 4 |
| Voltage according to EN 60309-2 | 230 V (50+60Hz) Blue | 230 V (50+60Hz) Blue |
| North America Voltage | 250 VAC | 250 VAC |
| Clock Hour Position | 9 hr | 9 hr |
| Identification Color | Blue | Blue |
| Ingress Protection | IP67 | IP67 |

All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437.