

PRODUCT DATA SHEET - IEC 60309

Part Number	312419
EAN	
Manufacturer	Walther-Werke
WEEE-Reg-Nr:	DE 22131895

20A 4P 480V 7H IP44 IEC Coupler

- High impact thermoplastic housing featuring high resistance and toughness creating an abrasion-resistant material
- Cable gland with "onion ring" neoprene bushing
- Retaining device
- Internal strain relief with "swing-away" feature
- Locking ring and gasket
- Zinc electroplated steel screws
- Shrouded pins
- Color coded by voltage
- Double terminal screws on all amperage devices
- Ground first to mate last to break for added safety
- Walther can produce and supply the mating cable assemblies.





Ordering/Logistics Information

Order Unit	Piece
Customs Number	8566990
Net Weight	0.44 lbs. or 0.197 kg
Packing Quantity (VPE)	10
Packaging Length	12.21 in or 0.31 m
Packaging Width	6.42 in or 0.163 m
Packaging Depth	5.45 in or 0.113 m
Gross Weight (VPE)	4.59 lbs. or 2.082 kg

Certification

2.672

UL certification	E329476 (U) LISTED
VDE certification	123016
EAC certification	BY112.02.01.020 06101
CSA certification	70096522





Classification system

Classification system	ETIM_6.0	
ETIM Class	EC001320	

Technical Product Data

IEC-amperage	16 A			
Amperage according to UL/CSA (for UL-version)	20 A			
Number of poles and wires	4 = 3P + G			
Voltage according to EN 60309-2	480 V - (50+60Hz) red			
Clock hour position	7 h			
Identification color	Red			
RAL Number	3000			
Maximum Cable diameter	0.82 in or 20.82 mm			
Cable strip length	1.18 in +/- 0.1 in or 30 mm +/- 2.5 mm			
Maximum torque terminal screw	0.8 Nm			
Degree of protection (IP)	IP44			
Connection system	Screwed terminal			
Contact material	Nickel-plated brass			
Cable entry	Swivel			
Angle of plug	Straight			
Material	Plastic			
Inflammability class of insulation material according to with UL94	V2			





Amp. Pole	16			32			63		
	3	4	5	3	4	5	3	4	5
d	135	151	151	171	171	171	255	255	255
Øe	51	65	65	72	72	72	96	96	96
f	68	85	85	91	91	98	114	114	114
m	110	113	113	136	136	136	194	194	194
Øp	7,5-14,5	7,5-14,5	7,5-14,5	10-19,5	10-19,5	10-19,5	18-34,5	18-34,5	18-34,5

All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437.