

PRODUCT DATA SHEET

Part Number	319419
EAN	
Manufacturer	Walther-Werke
WEEE-Reg-Nr:	DE 22131895

16A -20A 4P 480V 7H IP67 IEC Coupler

- High impact thermoplastic housing featuring high resistance
 And toughness creating an abrasion-resistant material
- Zinc electroplated steel screws
- Shrouded pins
- Color coded by voltage
- Double terminal screws on all amperage devices
- Ground first to mate last to break for added safety
- Walther can produce and supply the mating cable assemblies.



Ordering/Logistics Information

Order Unit	Piece	
Customs Number	8566990	
Net Weight	0.589 lbs or 0.267 kg	
Packing Quantity (VPE)	10	
Packaging Length	12.21 in or 0.31 m	
Packaging Width	10.04 in or 0.255 m	
Packaging Depth	5.90 in or 0.15 m	
Gross Weight (VPE)	6.21 lbs or 2.818 kg	

Certification

UL certification	E329476
VDE/ENEC certification	123016
EAC certification	BY112.02.01.020 06101


Classification system

Classification system	ETIM 6.0
Classification system	LTIIVI_0.0



ETIM Class EC0001320

_	
IEC-amperage	16 A
Amperage according to UL/CSA (for UL-version)	20 A
Number of poles and wires	4 = 3P + G
Voltage according to EN 60309-2	480 V (50+60Hz) red
Clock hour position	7 h
Identification color	Red
Maximum Cable diameter	0.73 in or 18.5 mm
Cable strip length	1 .38 in +/- 0.1 in or 35 mm +/- 2.5 mm
Maximum torque terminal screw	0.8 Nm
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Contact material	Nickel-plated brass
Cable entry	Swivel
Angle of plug	Straight
Material	Plastic



Inflammability class of insulation material according to with UL94

Amp.	16	16	32	32
Pole	4	5	3/4	5
d	150-161	150-161	174-183	174-183
Øe	Ø 65	Ø 65	Ø 72	Ø 72
f	85	92	95	104
m	125	125	142	142
Øu	Ø81	Ø 89	Ø 95	Ø 100
Øn	7.5 - 18.5	7.5 - 18.5	10 - 22.5	10-22.5

V2

All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437.