

## PRODUCT DATA SHEET

Part Number	t Number 319509	
EAN	4015609016563	
Manufacturer	Walther-Werke	
WEEE-Reg-Nr:	DE 22131895	

#### 16A 5P 230V 9H IP67 IEC Coupler

- High impact thermoplastic housing featuring high resistance
  And toughness creating an abrasion-resistant material
- Zinc electroplated steel screws
- Shrouded pins
- Color coded by voltage
- Double terminal screws on all amperage devices
- Ground first to mate last to break for added safety
- Walther can produce and supply the mating cable assemblies.



## Ordering/Logistics Information

Order Unit	Piece	
Customs Number	8566990	
Net Weight	0.66 lbs or 0.2982 kg	
Packing Quantity (VPE)	10	
Packaging Length	12.21 in or 0.31 m	
Packaging Width	10.04 in or 0.255 m	
Packaging Depth	5.90 in or 0.15 m	
Gross Weight (VPE)	7.01 lbs or 3.178 kg	

#### Certification

UL certification	E329476 Wussel
VDE/ENEC certification	123016
EAC certification	BY112.02.01.020 06101


# Classification system

Classification system	ETIM 6.0	
Glassification system	21111_010	



ETIM Class EC0001320

IEC-amperage	16 A	
Amperage according to UL/CSA (for UL-version)	20 A	
Number of poles and wires	5 = 3P + N + G	
Voltage according to EN 60309-2	230 V (50+60Hz) red	
Clock hour position 9 h		
Identification color	Blue	
RAL-number	5002	
Maximum Cable diameter	0.73 in or 18.5 mm	
Cable strip length	1 .38 in +/- 0.1 in or 35 mm +/- 2.5 mm	
Maximum torque terminal screw	0.8 Nm	
Degree of protection (IP)	IP67	
Connection system Screwed terminal		
Contact material Nickel-plated brass		
Cable entry	Swivel	
Angle of plug	Straight	
Material	Plastic	
Inflammability class of insulation material according to with UL94	V2	



Amp.	16	16	32	32
Pole	4	5	3/4	5
d	150-161	150-161	174-183	174-183
Øe	Ø 65	Ø 65	Ø 72	Ø 72
f	85	92	95	104
m	125	125	142	142
Øu	Ø81	Ø 89	Ø 95	Ø 100
Øр	7,5 - 18,5	7,5 - 18,5	10 - 22,5	10-22,5

All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437.