

## PRODUCT DATA SHEET

Part Number	361
EAN	401560900524
Manufacturer	Walther-Werke
WEEE-Reg-Nr:	DE 22131895

#### 63A 5P 380-415V 6H IP44 IEC Coupler

- High impact thermoplastic housing featuring high resistance. And toughness creating an abrasion-resistant material.
- Cable gland with "onion ring" neoprene bushing
- Retaining device
- Internal strain relief with "swing-away" feature
- Locking ring and gasket
- Zinc electroplated steel screws
- Shrouded pins
- Color coded by voltage.
- Double terminal screws on all amperage devices
- Ground first to mate last to break for added safety.
- Walther can produce and supply mating cable assemblies.



#### Ordering/Logistics Information

Order Unit	Piece
Customs Number	
Net Weight	1.69 lbs. or 0.7654 kg
Packing Quantity (VPE)	5
Packaging Length	12.21 in or 0.31 m
Packaging Width	10.04 in or 0.255 m
Packaging Depth	5.91 in or 0.15 m
Gross Weight (VPE)	8.87 lbs. or 4.023 kg

### Classification system

Classification system	ETIM_6.0
ETIM Class	EC001320

#### Certification





VDE certification	40000699
EAC certification	BY112.02.01.020 06101
UL certification	E329476 <b>W</b> uster

And multiple international certifications

# Technical Product Data

IEC-amperage	63 A			
Amperage according to UL/CSA (for UL-version)	60 A			
Number of poles and wires	5 = 3P + N + G			
Voltage according to EN 60309-2	380-415 V (50+60Hz)			
Clock hour position	6 h			
Identification color	Red			
Cable diameter	0.71 – 1.36 in or 18 – 34.5 mm			
Cable strip length	2.36 in +/- 0.1 in or 60 mm +/- 2.5 mm			
Cable ferrules length	0.47 in +/- 0.04 in or 12 mm +/- 1 mm			
Maximum torque terminal screw	2 Nm			
Maximum torque back shell	2.5 Nm			
Degree of protection (IP)	IP44			
Connection system	Screwed terminal			
Contact material	Brass standard			
Cable entry	Swivel			
Angle of plug	Straight			
Material	Plastic			
Inflammability class of insulation material according to with UL94	V2			





Amp. Pole	16			32			63		
	3	4	5	3	4	5	3	4	5
d	135	151	151	171	171	171	255	255	255
Øe	51	65	65	72	72	72	96	96	96
f	68	85	85	91	91	98	114	114	114
m	110	113	113	136	136	136	194	194	194

All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437.