

# PRODUCT DATA SHEET

Part Number	261409
EAN	4015609014859
Manufacturer	Walther-Werke
WEEE-Reg-Nr:	DE 22131895

#### 60A Plug 4P 250V 9h IP44

- High impact thermoplastic housing featuring high resistance
  And toughness creating an abrasion-resistant material
- Cable gland with "onion ring" neoprene bushing
- Retaining device
- Internal strain relief with "swing-away" feature
- Locking ring and gasket
- Zinc electroplated steel screws
- Shrouded pins
- Color coded by voltage
- Double terminal screws on all amperage devices
- Ground first to mate last to break for added safety
- Walther can produce and supply the mating cable assemblies.



## Ordering/Logistics Information

Order Unit	Piece
Customs Number	85366990
Net Weight	1.25 lbs or 0.566 kg
Packing Quantity (VPE)	5
Packaging Length	12.21 in or 0.31 m
Packaging Width	10.04 in or 0.255 m
Packaging Depth	5.91 in or 0.15 m
Gross Weight (VPE)	6.67 lbs or 3.026 kg

#### Conformities

CE Conformity	Υ
RoHS directive	2011/65/EU
RoHS directive	2015/863/EU
REACH regulation	1907/2006





## Certification

VDE certification	40000693
UL certification	E329476 U) LISTED
EAC certification	BY112.02.01.020.06090

### **Technical Product Data**

IEC-amperage	63 A			
Amperage according to UL/CSA (for UL-version)	60 A			
Number of poles and wires	4 = 3P + G			
Voltage according to EN 60309-2 250 V (50+60Hz)				
Clock hour position	9 h			
Identification color	Blue			
Cable diameter	0.71 in – 1.38 in or 18 mm - 35 mm			
Cable strip length	2.36 in +/- 0.1 in or 60 mm +/- 2.5 mm			
Cable ferrules length	0.47 in +/- 0.04 in or 12 mm +/- 1 mm			
Maximum torque terminal screw	2 Nm			
Maximum torque back shell	2.5 Nm			
Degree of protection (IP)	IP44			
Connection system Screwed terminal				
Contact material	Nickel-plated brass			
Cable entry Swivel				
Angle of plug	Straight			
Material	Plastic			
Inflammability class of insulation material according to with	V2			
UL94				





Amp. Pole	16		32			63			
	3	4	5	3	4	5	3	4	5
d	135	151	151	171	171	171	255	255	255
Øe	51	65	65	72	72	72	96	96	96
f	68	85	85	91	91	98	114	114	114
m	110	113	113	136	136	136	194	194	194

All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437.