



WALTHER-WERKE

FORTSCHRITT SEIT 1897

CUSTOM PDU, 60A, 3-PH, 3-Pole, 5-Wire, UL Listed

PART NO: 64910613501

FEATURES AND BENEFITS

- ✦ Solid Rubber Enclosure, non-conductive, Compact, Robust, Portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- ✦ Walther can custom design configurations that meet your application requirements.
- ✦ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	60A, 120/208VAC, 3P+N+G
Environmental Rating	NEMA 3R
Input	(1) 60A IEC IP67, 3P+N+G Inlet
Output	(1) 30A L6-30R, 2P+G Rec. (1) 20A L6-20R, 2P+G Rec. (3) 20A Duplex, GFCI Rec.
Overcurrent Protection	(1) 30A 2-Pole, MCB (1) 20A 2-Pole, MCB (3) 20A 1-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 14"
Approximate Weight	21 lbs.

DESCRIPTION:

120/208VAC, Three Phase single tier PDU with **Input:** (1) 60A IEC60309 IP44, 3-Pole, 5 Wire Plug with 3-feet of 8-AWG, 5 Conductor type W cable, **Output:** (1) 30A Twist lock, L6-30R, 2-Pole, 3 Wire receptacle, (1) 20A Twist lock, L6-20R, 2-Pole, 3 Wire receptacle, (3) 20A Duplex GFCI receptacles protected by (1) 30A 2-Pole circuit breaker, (1) 20A 2-Pole circuit breaker, (3) 20A 1-Pole circuit breakers,

APPLICATION:

Construction Sites, Entertainment, ship building/Repair etc.

WALTHER ELECTRIC, INC.
12F/G WORLD'S FAIR DRIVE, SOMERSET, NJ 08873
(800) 925-8437 toll free | P (732) 537-9201 | F (732) 537-9209
WWW.WALTHERELECTRIC.COM | CUSTSERV@WALTHERELECTRIC.COM

