



WALTHER-WERKE

FORTSCHRITT SEIT 1897

CUSTOM PDU, 100A, 1-PH, 2-Pole, 4-Wire, UL Listed

PART NO: 649110IMN01

FEATURES AND BENEFITS

- ↪ Solid Rubber Enclosure , Non-conductive, UL Listed, compact, Robust, Portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV Resistant, NEMA 3R
- ↪ Walther can custom design configurations that meet your application requirements
- ↪ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	100A, 125/208VAC, 2P+N+G
Environmental Rating	NEMA 3R
Input	(1) 100A IEC60309 IP67 Inlet, 2P+N+G
Output	(2) 50A CS Type, 2P+N+G
Overcurrent Protection	(2) 50A 2-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 14"
Approximate Weight	19 lbs.

DESCRIPTION:

125/250VAC, Single Phase single tier PDU with **Input:** (1) 100A IEC60309 IP67, 2-Pole, 4 Wire inlet, **Output:** (2) 50A CS6369 CS Type, 2-Pole, 4 Wire receptacles protected by (2) 50A 2-Pole circuit breakers

APPLICATION:

Construction Sites, Entertainment, Convention Center, Shipyard etc.