

Custom PDU, 300A, 3-PH, 3-Pole, 5-Wire, UL Listed

PART NO: 649230C34

FEATURES AND BENEFITS

- Solid Rubber Enclosure, non-conductive, UL Listed, compact, robust, portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- Walther can custom design configurations that meet your application requirements.
- Walther can produce and supply the mating cable assemblies

Specifications	
Rating	300A, 250VAC, 3P+N+G
Environmental Rating	NEMA 3R
Input	(5) E16 Camloks,
	3P+N+G
Output	(6) 50A CS TYPE, 3P+G
	Receptacle
Overcurrent Protection	(6) 50A 3-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 19"
Approximate Weight	35 lbs.



DESCRIPTION:

250VAC, Three Phase double tier PDU with **Input**: (5) E16 Camloks, 3-Pole, 5 Wire, **Output**: (6) 50A CS Type, 3-Pole, 4 Wire receptacles with weather cover protected by (6) 50A 3-Pole circuit breakers

APPLICATION:

Construction sites, Entertainment, Ship building/Repair, etc.

