



CUSTOM PDU, 200A, 3-PH, 3-Pole, 5 Wire, UL Listed

PART NO: 649230CC

FEATURES AND BENEFITS

- ↪ Solid Rubber Enclosure , non-conductive, compact, robust, portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- ↪ Walther can custom design configurations that meet your application requirements.
- ↪ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	200A, 120/208V 3P+N+G
Environmental Rating	NEMA 3R
Input	(5) E16 Camlocks, 3P+N+G
Pass thru	(5) E16 Camlocks, 3P+N+G
Output	(6) 30A L21-30R, 3P+N+G. (1) 20A 5-20 Duplex
Overcurrent Protection	(6) 30A 3-Pole, MCB (3) 20A 1-Pole, MCB
Approximate Dimensions	L 11" W 12" H 25"
Approximate Weight	39 lbs.

DESCRIPTION:

200A/120-208V, Three Phase, double tier PDU with **Input:** (5) E16 Camlocks, 3-Pole, 5 Wire with indicator light for each phase, **Pass thru:** (5) E16 Camlocks, 3-Pole, 5 Wire with weather cover, **Output:** (6) 30A Twist lock, NEMA L21-30R, 3-Pole, 5 Wire receptacles, (1) 20A 5-20 Duplex receptacle protected by (6) 30A 3-Pole circuit breakers, (1) 20A 1-Pole circuit breaker

APPLICATION:

Construction sites, Entertainment, Convention center, Food industry, etc.