



Custom PDU, 300A, 3-PH, 3-Pole, 5 Wire, UL Listed

PART NO: 649230CU

FEATURES AND BENEFITS

- ✦ Solid Rubber Enclosure , non-conductive, UL Listed, compact, robust, portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- ✦ Walther can custom design configurations that meet your application requirements.
- ✦ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	300A, 120/208VAC, 3P+N+G
Environmental Rating	NEMA 3R
Input	(5) E16 Camlocks, 250VAC, 3P+N+G
Output	(8) 50A CS TYPE, 2P+N+G Receptacles
Overcurrent Protection	(8) 50A 2 Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 19"
Approximate Weight	39 lbs.

DESCRIPTION:

120/208VAC, Three Phase double tier PDU with **Input:** (5) E16 Camlocks, 3-Pole, 5 Wire, **Output:** (8) 50A CS Type, 2-Pole, 4 Wire receptacles with weather cover protected by (8) 50A 2-Pole circuit breakers

APPLICATION:

Construction sites, Entertainment, Ship building/Repair, etc.