



CUSTOM PDU 100A 3PH 3 Pole 5 Wire UL Listed

PART NO: 6493221

FEATURES AND BENEFITS

- ✦ Solid Rubber Enclosure , non-conductive, compact, robust, portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- ✦ Walther can custom design configurations that meet your application requirements.
- ✦ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	100A, 120/208VAC, 3P+N+G
Environmental Rating	NEMA 3R
Input	(1) IEC IP67, 3P+N+G
Output	(4) 50A CS Type rec. (2) 30A L5-30R (4) 20A Duplex, GFCI
Overcurrent Protection	(4) 50A 2-Pole, MCB (2) 30A 1-Pole, MCB (4) 20A 1-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 25"
Approximate Weight	45 lbs.

DESCRIPTION:

120/208VAC, Three Phase three tier PDU with **Input:** (1) IEC60309 IP67, 3-Pole, 5 Wire inlet , **Output:** (4) 50A CS Type, 2-Pole 4 Wire receptacles, (2) 30A Twist lock, NEMA L5-30R, 1-Pole 3 Wire receptacles, (4) 20A 5-20 Duplex GFCI protected by (4) 60A 3-Pole circuit breakers, (2) 30A 1-Pole circuit breakers, (4) 20A 1-Pole circuit breakers

APPLICATION:

Construction sites, Entertainment, Convention center, Food industry, etc.