



## CUSTOM PDU, 50A, 1-PH, 2-Pole, 4-Wire, UL Listed

### PART NO: HEB201L

#### FEATURES AND BENEFITS

- ✦ Solid Rubber Enclosure, non-conductive, Compact, Robust, Portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- ✦ Walther can custom design configurations that meet your application requirements.
- ✦ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	50A, 120/208VAC, 2P+N+G
Environmental Rating	NEMA 3R
Input	(1) 50A CS Type 2P+N+G
Output	(6) 20A Duplex GFCI
Overcurrent Protection	(6) 20A 1-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 14"
Approximate Weight	19 lbs.

#### DESCRIPTION:

120/208VAC, Single Phase one tier PDU with **Input:** (1) 50A Twist lock, CS6375, 2-Pole, 4 Wire inlet, **Output:** (6) 20A Duplex GFCI receptacles with weather cover protected by (6) 20A 1-Pole circuit breakers

#### APPLICATION:

Construction Sites, Entertainment, ship building/Repair etc.