

CUSTOM PDU, 50A, 1-PH, 2-Pole, 4-Wire, UL Listed

PART NO: HEB201X2U

FEATURES AND BENEFITS

- Solid Rubber Enclosure, non-conductive, Compact, Robust, Portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant
- Walther can custom design any configurations based on Customer's application
- Walther can produce and supply the mating cable assemblies

Specifications	
Rating	50A, 120/208V, 2P+N+G
Environmental Rating	Indoor use
Input	(1) 50A CS Type 2P+N+G Inlet
Output	(1) 50A 14-50R Receptacle
	(6) 20A 5-20R Duplex
Overcurrent Protection	(1) 50A 2-Pole <i>,</i> MCB (Main)
	(6) 20A 1-Pole <i>,</i> MCB
Approximate Dimensions	L 11.5" W 12.5" H 14"
Approximate Weight	19 lbs.



DESCRIPTION:

50A, 120/208V, Single Phase one tier PDU with **Input:** (1) 50A Twist lock, CS6375, 2-Pole, 4 Wire inlet, **Output:** (1) 50A 14-50R, 2-Pole, 4 Wire Receptacle, (6) 20A NEMA 5-20R Duplex with weather cover receptacles protected by (1) 50A 2-Pole circuit breaker, (6) 20A 1-Pole circuit breakers

APPLICATION:

Construction Sites, Entertainment, ship building/Repair etc.

