

CUSTOM PDU, 40A, 3-PH, 3-Pole, 5-Wire, UL Listed

PART NO: HEB3102AU

FEATURES AND BENEFITS

Solid Rubber Enclosure, non-conductive, Compact, Robust, Portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R

Walther can custom design configurations that meet your application requirements.

Walther can produce and supply the mating cable assemblies

Specifications	
Rating	40A, 120/208VAC,
	3P+N+G
Environmental Rating	NEMA 3R
Input	(5) E16 Camloks,
	3P+N+G
Output	(6) 20A 5-20R Duplex
	Rec.
Overcurrent Protection	(6) 20A 1-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 14"
Approximate Weight	19 lbs.



120/208VAC, Three Phase one tier PDU with **Input:** (5) E16 Camloks, 3-Pole, 5 Wire, **Output:** (6) 20A NEMA 5-20 Duplex receptacles with weather cover protected by (6) 20A 1-Pole circuit breakers

APPLICATION:

Construction Sites, Entertainment, Ship building/Repair etc.

