



Custom PDU 80A 3PH 3 pole 5 wire UL Listed

PART NO: HEB3106U

FEATURES AND BENEFITS

- ↪ Solid Rubber Enclosure , non-conductive, UL Listed, compact, robust, portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- ↪ Walther can custom design configurations that meet your application requirements.
- ↪ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	80A, 120/208VAC, 3P+N+G
Environmental Rating	NEMA 3R
Input	(5) E16 Camlocks, 3P+N+G
Pass thru	(5) E16 Camlocks, 3P+N+G
Output	(12) 20A Duplex, GFCI Rec.
Overcurrent Protection	(12) 20A 1-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 19"
Approximate Weight	35 lbs.

DESCRIPTION:

120/208VAC, Three Phase double tier PDU with **Input:** of (5) E16 Camlocks, 3-Pole, 5 Wire, **pass thru:** (5) E16 Camlocks, 3-Pole, 5Wire with weather cover, **Output:** (12) 20A, NEMA 5-20 Duplex GFCI , 1-Pole, 3 Wire receptacles with weather cover protected by (12) 20A, 1-Pole circuit breaker.

APPLICATION:

Construction Sites, Entertainment, Convention Center, Ship yard, etc.