



Custom PDU, 60A, 3-PH, 3-Pole, 5-Wire, UL Listed

PART NO: HEB32601

FEATURES AND BENEFITS

- ✦ Solid Rubber Enclosure , non-conductive, UL Listed, compact, robust, portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- ✦ Walther can custom design configurations that meet your application requirements.
- ✦ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	60A, 120/208VAC, 3P+N+G
Environmental Rating	NEMA 3R
Input	(1)60A IEC IP67, 3P+N+G
Output	(4) 30A L21-30R, 3P+N+G Receptacle
Overcurrent Protection	(4) 30A 3-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 19"
Approximate Weight	32 lbs.

DESCRIPTION:

120/208VAC, Three Phase double tier PDU with **Input:** of (1) 60A IEC60309 IP67, 3-Pole, 5 Wire inlet, **Output:** (4) 30A Twist lock, NEMA L21-30R, 3-Pole, 5 Wire receptacles, protected by (4) 30A 3-Pole circuit breaker.

APPLICATION:

Construction Sites, Entertainment, Convention Center, Ship yard, etc.