



WALTHER-WERKE

FORTSCHRITT SEIT 1897

CUSTOM PDU, 40A, 3-PH, 3-Pole, 5-Wire, UL Listed

PART NO: HEB361U

FEATURES AND BENEFITS

- ↻ Solid Rubber Enclosure, non-conductive, Compact, Robust, Portable with top mounted handle, Internal breakers are protected by a transparent hinged cover, Black in color can be used in nuclear facilities, Stackable, UV resistant, NEMA 3R
- ↻ Walther can custom design configurations that meet your application requirements.
- ↻ Walther can produce and supply the mating cable assemblies



Specifications	
Rating	40A, 120/208VAC, 3P+N+G
Environmental Rating	NEMA 3R
Input	(1) 60A IEC60309 IP67, 3P+N+G Inlet
Output	(6) 20A 5-20R Duplex Rec.
Overcurrent Protection	(6) 20A 1-Pole, MCB
Approximate Dimensions	L 11.5" W 12.5" H 14"
Approximate Weight	19 lbs.

DESCRIPTION:

120/208VAC, Three Phase one tier PDU with **Input:** (1) 60A IEC60309 IP67, 3-Pole, 5 Wire inlet, **Output:** (6) 20A NEMA 5-20 Duplex receptacles with weather cover protected by (6) 20A 1-Pole circuit breakers

APPLICATION:

Construction Sites, Entertainment, Ship building/Repair etc.