

## PDU 50A, 1-PH, 2-Pole, 4 Wire, UL Listed

MPN: **HEB202U**

### FEATURES & BENEFITS

- Compact Solid Rubber Enclosure, non-conductive, offering good resilience and tensile strength. Outstanding resistance to abrasion and fatigue
- Overcurrent Protection included to prevent excessive amounts of current or a short circuit
- Space-saving design for easy storage stacking
- Walther can design and manufacture mating cable assemblies



### SPECIFICATIONS

<b>Rating</b>	50A, 120/208VAC, 2P+N+G
<b>Environmental Rating</b>	NEMA 3R
<b>Input</b>	(1) 50A CS Type 2P+N+G Inlet
<b>Output</b>	(1) 50A CS Type 2P+N+G Rec., (1) 30A L6-30R (3) 20A Duplex GFCI
<b>Overcurrent Protection</b>	(1) 50A 2-Pole, MCB, (1) 30A 2-Pole, MCB (3) 20A 1-Pole, MCB
<b>Dimensions</b>	L 11.5" W 12.5" H 14"
<b>Weight</b>	19 lbs.

### DESCRIPTION

50A, 120/208VAC, Single Phase one tier PDU with Input: (1) 50A CS-Type CS6375 2-Pole, 4 Wire inlet, Output: (1) 50A CS-Type, CS6369, 2-Pole, 4 Wire receptacle with weather cover, (1) 30A Twist lock, L6-30R, 2-Pole, 3 Wire receptacle, (3) 20A Duplex GFCI receptacles protected by (1) 50A 2-Pole breaker (main), (1) 30A 2-Pole circuit breaker, (3) 20A 1-Pole circuit breakers


### APPLICATION

Construction Sites, Entertainment, ship building/Repair etc.


*NOTE: All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437*

## HEB202U Technical Drawing

**PROTECTION:**  
 (1) 50A 2P MCB  
 (1) 30A 2P MCB  
 (3) 20A 1P MCB



FRONT




BACK


**INPUT:**  
 50A INLET CS6375  
 120/250V 2P+N+G

**PASSTHRU:**  
 50A CS6369 W/COVER  
 120/250V 2P+N+G

**OUTPUT:**  
 (3) 20A GFCI DPX



RIGHT



LEFT

**OUTPUT:**  
 (1) 30A L6-30R

