

PDU 50A, 1-PH, 2-Pole, 4 Wire, UL Listed

MPN: **HEB203U**

FEATURES & BENEFITS

- Compact Solid Rubber Enclosure, non-conductive, offering good resilience and tensile strength. Outstanding resistance to abrasion and fatigue
- Overcurrent Protection included to prevent excessive amounts of current or a short circuit
- Space-saving design for easy storage stacking
- Walther can design and manufacture mating cable assemblies



SPECIFICATIONS	
Rating	50A, 120/208VAC, 2P+N+G
Environmental Rating	NEMA 3R
Input	(1) 50A CS Type 2P+N+G Inlet
Output	(1) 50A CS Type 2P+N+G Rec., (2) 30A L6-30R (3) 20A Duplex GFCI,
Overcurrent Protection	(1) 50A 2-Pole, MCB, (2) 30A 2-Pole, MCB (3) 20A 1-Pole, MCB
Dimensions	L 11.5" W 12.5" H 14"
Weight	19 lbs.

DESCRIPTION

50A, 120/208VAC, Single Phase one tier PDU with Input: (1) 50A CS-Type CS6375 2-Pole, 4 Wire inlet, Output: (1) 50A CS-Type, CS6369, 2-Pole, 4 Wire receptacle with weather cover, (2) 30A Twist lock, L6-30R, 2-Pole, 3 Wire receptacles, (3) 20A Duplex GFCI receptacles protected by (1) 50A 2-Pole breaker (main), (2) 30A 2-Pole circuit breakers, (3) 20A 1-Pole circuit breakers

APPLICATION

Construction Sites, Entertainment, ship building/Repair etc.

NOTE: All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437

HEB203U Technical Drawing

