

PDU 60A, 3-PH, 3-Pole, 5 Wire, UL Listed

MPN: **HEB364U**

FEATURES & BENEFITS

- Compact Solid Rubber Enclosure, non-conductive, offering good resilience and tensile strength· Outstanding resistance to abrasion and fatigue
- Overcurrent Protection included to prevent excessive amounts of current or a short circuit
- Space-saving design for easy storage stacking
- Walther can design and manufacture mating cable assemblies



SPECIFICATIONS	
Rating	60A, 120/208VAC, 3P+N+G
Environmental Rating	NEMA 3R
Input	(1) 60A IEC IP67, 3P+N+G angled inlet
Output	(3) 20A Duplex GFCI, (2) 30A L21-30R Rec.
Overcurrent Protection	(3) 20A 1-Pole, MCB, (2) 30A 3-Pole, MCB
Dimensions	L 11.5" W 12.5" H 14"
Weight	19 lbs.

DESCRIPTION

60A, 120/208V, Three Phase one tier PDU with **Input:** (1) 60A IEC60309 IP67, 3-Pole, 5 Wire 80° angled inlet, **Output:** (3) 20A Duplex GFCI receptacles with weather, (2) 30A Twist lock, NEMA L21-30R, 3-Pole, 5 Wire with weather cover protected by (3) 20A 1-Pole circuit breakers, (2) 30A 3-Pole circuit breakers

APPLICATION

Construction Sites, Entertainment, ship building/Repair etc.

NOTE: All specifications are subject to change without notice. Consult a Walther Electric Engineer for the latest specifications or speak with a member of our Customer Care Team +1 (800) 925-8437

HEB364U Technical Drawing

